



CFX 3060 FURNACE COOLANT HOSE C/W ISOTHERM COVER 1050 KPA

DESIGNED TO CONVEY COOLING WATER IN STEEL MILLS, WHERE A HOSE IS REQUIRED TO WITHSTAND HEAT RADIATION, OPEN FLAME AND SPLASHES OF WHITE-HOT METAL

SUPPLIED WITH PLAIN OR FLANGED ENDS.

TEMPRETURE RANGE
-35 DEG C TO +500 DEG C

CONSTRUCTION

LINER
RED, SMOOTH NON - CONDUCTIVE RUBBER

REINFORCING
MULTIPLE PLYS OF SYNTHETIC FABRIC.

COVER
SINGLE PLY OF RUBBER IMPREGNATED HOSE SHEILD

HOSE SHEILD CAN WITHSTAND RADIANT TEMPRETURE OF 500 - 600 DEG C

SIZE NOM	SIZE ACT	APPROX O.D	LENGTH
25 NB	25.40 MM	49 MM	30 MET
32 NB	31.75 MM	56 MM	30 MET
40 NB	38.10 MM	58 MM	30 MET
50 NB	50.80 MM	74 MM	30 MET
65 NB	63.50 MM	89 MM	30 MET
80 NB	76.20 MM	100 MM	20 MET
100 NB	101.60 MM	126 MM	20 MET
125 NB	127.00 MM	151 MM	20 MET
150 NB	152.40 MM	176 MM	20 MET
200 NB	203.20 MM	226 MM	15 MET